

---

# **ign\_rndf Documentation**

***Release 0.0.1***

**Open Source Robotics Foundation**

**Apr 15, 2020**



---

## Contents

---

<b>1</b>	<b>What is Ignition RNDF?</b>	<b>3</b>
<b>2</b>	<b>Installation</b>	<b>5</b>
2.1	Ubuntu Linux . . . . .	5
2.2	Mac OS X . . . . .	5
2.3	Windows . . . . .	6
2.4	Install from sources (Ubuntu Linux) . . . . .	7
<b>3</b>	<b>How to contribute</b>	<b>11</b>
3.1	Development process . . . . .	11
3.2	Debugging Ignition RNDF . . . . .	14
3.3	Code Check . . . . .	14
<b>4</b>	<b>API</b>	<b>17</b>
<b>5</b>	<b>Indices and tables</b>	<b>19</b>



Contents:



# CHAPTER 1

---

## What is Ignition RNDF?

---

Ignition RNDF is an open source library that allows to load a Route Network Definition File (RNDF). See the [RNDF spec](#) for a complete description of this road network format.

- What programming language can I use to interface Ignition RNDF?

C++ is our native implementation and so far the only way to use the library.



## CHAPTER 2

### Installation

Instructions to install Ignition RNDP on all the platforms supported: major Linux distributions, Mac OS X and Windows.

Next, you can see the major Ignition RNDP versions, their availability and lifetime.

Ver- sion	Available on Ubuntu directly	Available on Ubuntu via OSRF	Available on MacOS via Homebrew tap	Since	EOL
0.y	–	Ubuntu T, X	Yosemite, El Capitan	April 2017	April 2021

### 2.1 Ubuntu Linux

Setup your computer to accept software from *packages.osrfoundation.org*:

```
sudo sh -c 'echo "deb http://packages.osrfoundation.org/gazebo/ubuntu-stable\n`lsb_release -cs` main" > /etc/apt/sources.list.d/gazebo-stable.list'
```

Setup keys:

```
wget http://packages.osrfoundation.org/gazebo.key -O - | sudo apt-key add -
```

Install Ignition RNDP:

```
sudo apt-get update\nsudo apt-get install libignition-rndf0-dev
```

### 2.2 Mac OS X

Ignition RNDP and several of its dependencies can be compiled on OS X with [Homebrew](#) using the [osrf/simulation tap](#). Ignition RNDP is straightforward to install on Mac OS X 10.9 (Mavericks) or higher. Installation on older versions

requires changing the default standard library and rebuilding dependencies due to the use of c++11. For purposes of this documentation, I will assume OS X 10.9 or greater is in use. Here are the instructions:

Install Homebrew, which should also prompt you to install the XCode command-line tools:

```
ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/
↪install)"
```

Run the following commands:

```
brew tap osrf/simulation
brew install ignition-rndf0
```

## 2.3 Windows

At this moment, compilation has been tested on Windows 7 and 8.1 and is supported when using [Visual Studio 2013](#). Patches for other versions are welcome.

This installation procedure uses pre-compiled binaries in a local workspace. To make things easier, use a MinGW shell for your editing work (such as the [Git Bash Shell with Mercurial](#)), and only use the Windows cmd for configuring and building. You might also need to [disable the Windows firewall](#).

Make a directory to work in, e.g.:

```
mkdir ign-ws
cd ign-ws
```

Clone and prepare the Ignition Math dependency:

```
hg clone https://bitbucket.org/ignitionrobotics/ign-math -b ign-math2
cd ign-math
mkdir build
```

In a Windows Command Prompt, load your compiler setup, e.g.:

```
"C:\Program Files (x86)\Microsoft Visual Studio 12.0\VC\vcvarsall.bat" amd64
```

In the Windows Command Prompt, configure and build:

```
cd ign-math\build
..\configure
nmake install
```

Clone Ignition RNDF:

```
cd ..\..\
hg clone https://bitbucket.org/ignitionrobotics/ign-rndf
cd ign-rndf
```

Configure and build:

```
mkdir build
cd build
..\configure
nmake
nmake install
```

You should now have an installation of ign-rndf in ign-ws/ign-rndf/build/install.

Now build the examples:

```
cd ../example
mkdir build
cd build
../configure
nmake
```

Now try an example. In one Windows terminal run:

```
rndf_info <_your_rndf_file>
```

## 2.4 Install from sources (Ubuntu Linux)

For compiling the latest version of Ignition RNDF you will need an Ubuntu distribution equal to 14.04 (Trusty) or newer.

Make sure you have removed the Ubuntu pre-compiled binaries before installing from source:

```
sudo apt-get remove libignition-rndf0-dev
```

Setup your computer to accept software from *packages.osrfoundation.org*:

```
sudo sh -c 'echo "deb http://packages.osrfoundation.org/gazebo/ubuntu-stable
`lsb_release -cs` main" > /etc/apt/sources.list.d/gazebo-stable.list'
```

Setup keys:

```
wget http://packages.osrfoundation.org/gazebo.key -O - | sudo apt-key add -
```

Install prerequisites. A clean Ubuntu system will need:

```
sudo apt-get update
sudo apt-get install cmake pkg-config python ruby-ronn
```

Clone and prepare the Ignition Math dependency:

```
hg clone https://bitbucket.org/ignitionrobotics/ign-math -b ign-math2 /tmp/ign-math
cd /tmp/ign-math
mkdir build
cd build
```

Configure and build:

```
cmake ..
make -j4
sudo make install
```

Clone the repository into a directory and go into it:

```
hg clone https://bitbucket.org/ignitionrobotics/ign-rndf /tmp/ign-rndf
cd /tmp/ign-rndf
```

Create a build directory and go there:

```
mkdir build
cd build
```

Configure Ignition RNDF (choose either method a or b below):

A. Release mode: This will generate optimized code, but will not have debug symbols. Use this mode if you don't need to use GDB.

```
cmake ../
```

Note: You can use a custom install path to make it easier to switch between source and debian installs:

```
cmake -DCMAKE_INSTALL_PREFIX=/home/$USER/local ../
```

B. Debug mode: This will generate code with debug symbols. Ignition RNDF will run slower, but you'll be able to use GDB.

```
cmake -DCMAKE_BUILD_TYPE=Debug ../
```

The output from `cmake ../` may generate a number of errors and warnings about missing packages. You must install the missing packages that have errors and re-run `cmake ../`. Make sure all the build errors are resolved before continuing (they should be there from the earlier step in which you installed prerequisites).

Make note of your install path, which is output from `cmake` and should look something like:

```
-- Install path: /home/$USER/local
```

Build Ignition RNDF:

```
make -j4
```

Install Ignition RNDF:

```
sudo make install
```

If you decide to install Ignition RNDF in a local directory you'll need to modify your `LD_LIBRARY_PATH`:

```
echo "export LD_LIBRARY_PATH=<install_path>/local/lib:$LD_LIBRARY_PATH" >> ~/.bashrc
```

Now build the examples:

```
cd ../
mkdir build
cd build
cmake ..
make
```

Now try an example. In a terminal run:

```
rndf_info <_your_rndf_file>
```

### 2.4.1 Uninstalling Source-based Install

If you need to uninstall Ignition RNDF or switch back to a debian-based install when you currently have installed the library from source, navigate to your source code directory's build folders and run `make uninstall`:

```
cd /tmp/ign-rndf/build  
sudo make uninstall
```



Ignition RNDP is an open source project based on the Apache License Version 2.0, and is maintained by hardworking developers for everyone's benefit. If you would like to contribute software patches, read on to find out how.

### 3.1 Development process

We follow a development process designed to reduce errors, encourage collaboration, and make high quality code. The process may seem rigid and tedious, but every step is worth the effort (especially if you like applications that work).

#### 3.1.1 Steps to follow

1. Are you sure? Has your idea already been done, or maybe someone is already working on it?

Check the [issue tracker](#).

2. [Fork Ignition RNDP](#). This will create your own personal copy of the project. All of your development should take place in your fork.

3. Work out of a branch:

```
hg branch my_new_branch_name
```

Always work out of a new branch, never off of *default*. This is a good habit to get in, and will make your life easier. If you're solving an issue, make the branch name `issue_` followed by the issue number. E.g.: `issue_23`.

4. Write your code.

This is the fun part.

5. Write tests.

A pull request will only be accepted if it has tests. See the *Test coverage* section below for more information.

6. Compiler warnings.

Code must have zero compile warnings.

7. Style.

A tool is provided to check for correct style. Your code must have no errors after running the following command from the root of the source tree:

```
sh tools/code_check.sh
```

The tool does not catch all style errors. See the *Style* section below for more information.

8. Tests pass.

There must be no failing tests. You can check by running `make test` in your build directory.

9. Documentation.

Document all your code. Every class, function, member variable must have doxygen comments. All code in source files must have documentation that describes the functionality. This will help reviewers, and future developers.

10. Review your code.

Before submitting your code through a pull request, take some time to review everything line-by-line. The review process will go much faster if you make sure everything is perfect before other people look at your code. There is a bit of the human-condition involved here. Folks are less likely to spend time reviewing your code if it's bad.

11. Small pull requests.

A large pull request is hard to review, and will take a long time. It is worth your time to split a large pull request into multiple smaller pull requests. For reference, here are a few examples:

- [Small, very nice](#)
- [Medium, still okay](#)
- [Too large](#)

12. [Pull request](#).

Submit a pull request when you ready.

13. Review.

At least two other people have to approve your pull request before it can be merged. Please be responsive to any questions and comments.

14. Done, phew.

Once you have met all the requirements, your code will be merged. Thanks for improving Ignition RNDF!

### 3.1.2 Style

In general, we follow [Google's style guide](#). However, we add in some extras.

**“this” pointer** All class attributes and member functions must be accessed using the `this->` pointer. Here is an [example](#).

**Underscore function parameters** All function parameters must start with an underscore. Here is an [example](#).

**Do not cuddle braces** All braces must be on their own line. Here is an [example](#).

**Multi-line code blocks** If a block of code spans multiple lines and is part of a flow control statement, such as an `if`, then it must be wrapped in braces. Here is an [example](#)

**++ operator** This occurs mostly in `for` loops. Prefix the `++` operator, which is [slightly more efficient than postfix in some cases](#).

**PIMPL/Opaque pointer** If you are writing a new class, it must use a private data pointer. Here is an [example](#), and you can read more [here](#).

**const functions** Any class function that does not change a member variable should be marked as `const`. Here is an [example](#).

**const parameters** All parameters that are not modified by a function should be marked as `const`. This applies to parameters that are passed by reference, pointer, and value. Here is an [example](#).

**Pointer and reference variables** Place the `*` and `&` next to the variable name, not next to the type. For example: `int &variable` is good, but `int& variable` is not. Here is an [example](#).

**Camel case** In general, everything should use camel case. Exceptions include protobuf variable names.

**Class function names** Class functions must start with a capital letter, and capitalize every word.

```
void MyFunction() ; : Good
void myFunction() ; : Bad
void my_function() ; : Bad
```

**Variable names** Variables must start with a lower case letter, and capitalize every word thereafter.

```
int myVariable; : Good
int myvariable; : Bad
int my_variable; : Bad
```

### 3.1.3 Reduce Code Duplication

Check to make sure someone else is not currently working on the same feature, before embarking on a project to add something to Ignition RNDF. Check the [issue tracker](#) looking for issues with similar ideas.

#### 3.1.4 Write Tests

All code should have a corresponding unit test. Ignition RNDF uses [GTest](#) for unit testing.

##### Test coverage

The goal is to achieve 100% line and branch coverage. However, this is not always possible due to complexity issues, analysis tools misreporting coverage, and time constraints. Try to write as complete of a test suite as possible, and use the coverage analysis tools as guide. If you have trouble writing a test please ask for help in your pull request.

Ignition RNDF has a build target called `make coverage` that will produce a code coverage report. You'll need `lcov` installed.

1. In your `build` folder, compile Ignition RNDF with

```
-DCMAKE_BUILD_TYPE=Coverage:
```

```
cmake -DCMAKE_BUILD_TYPE=Coverage ..\
make
```

2. Run a single test, or all the tests:

```
make test
```

3. Make the coverage report:

```
make coverage
```

4. View the coverage report:

```
firefox coverage/index.html
```

## 3.2 Debugging Ignition RNDF

### 3.2.1 Meaningful backtraces

In order to provide meaningful backtraces when using a debugger, such as GDB, Ignition RNDF should be compiled with debugging support enabled. When using the ubuntu packages, specially the `-dbg` package, this support is limited but could be enough in most of the situations. This are the three level of traces which can be obtained:

**Maximum level of debugging support** This only can be obtained compiling Ignition RNDF from source and setting the `CMAKE_BUILD_TYPE` to `DEBUG`. This will set up no optimizations and debugging symbols. It can be required by developers in situations specially difficult to reproduce.

**Medium level of debugging support** This can be obtained installing the `libignition-rndf0-dbg` package or compiling Ignition RNDF from source using the `RELWITHDEBINFO` `CMAKE_BUILD_TYPE` mode (which is the default if no mode is provided). This will set up `-O2` optimization level but provide debugging symbols. This should be the default when firing up `gdb` to explore errors and submit traces.

**Minimum level of debugging support** This one is present in package versions (no `-dbg` package present) or compiling Ignition RNDF from source using the `RELEASE` `CMAKE_BUILD_TYPE` option. This will set up the maximum level of optimizations and does not provide any debugging symbol information. This traces are particularly difficult to follow.

## 3.3 Code Check

Code pushed into the repository should pass a few simple tests. It is also helpful if patches submitted through bitbucket pass these tests. Passing these tests is defined as generating no error or warning messages for each of the following tests.

### 3.3.1 Static Code Check

Static code checking analyzes your code for bugs, such as potential memory leaks, and style. The Ignition RNDF static code checker uses `cppcheck`, and a modified `cpplint`. You'll need to install `cppcheck` on your system. Ubuntu users can install via:

```
sudo apt-get install cppcheck
```

To check your code, run the following script from the root of the Ignition RNDF sources:

```
sh tools/code_check.sh
```

It takes a few minutes to run. Fix all errors and warnings until the output looks like:

```
Total errors found: 0
```



## CHAPTER 4

---

### API

---

Please, visit [this link](#) for version 0.x.



## CHAPTER 5

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`